

**Compressore Bicilindrico 24V DC**

Interamente in metallo e montato su cuscinetti a sfera, garantisce prestazioni professionali con il minimo ingombro.



**Two Cylinder Compressor 24V DC**

All-metal construction, assembled in ball bearings, ensures professional performances with minimum sizes.

**CODICE :GRU24BCC40DG**



**DATI TECNICI**

Cilindrata	cmc 40			
Giri/minuto	2582			
	l/min.	cfm	bar	psi
Aria Aspirata/Aria Resa	104/76	2.67	a 2	29
	102/57	2.02	a 6	87
	102/49	1.74	a 8	116
Pressione max 12 bar			a 12	174
Assorbimento Max	Amp 20			
Potenza media assorbita	Watt 423			
Classe di protezione	IP 20			
Classe di servizio	S 1			
Rumorosità	Db 68			
Dimensioni compressore	Cm 30 x 11 x h17			
Peso compressore	Kg 7			

Raccomandato per uso a ciclo continuo




**TECHNICAL DATA**

Swept	cmc 40			
Rpm	2582			
	l/min.	cfm	bar	psi
Air Displacement/Air Delivered	104/76	2.67	at 2	29
	102/57	2.0	at 6	87
	102/49	1.74	at 8	116
Max pressure 12 bar			at 12	174
Max Amp. absorption	Amp 20			
Average power absorption	Watt 423			
Protection class	IP 20			
Service class	S 1			
Noise level	Db 68			
Compressor dimensions	Cm 30 x 11 x h17			
Compressor weight	Kg 7			

continuous cycle to work: Max 60'

I dati sono suscettibili di modifiche senza preavviso - The company reserves the right to change any element without notice.

**- ALCUNE VERSIONI / SOME MODELS-**



**GRU24BCC40DGDIR** 30x15xh17 Kg.8



**GRU24BCC40DGDIRF** 30x25xh17 Kg.9



**ELECOM24BCLT5DGF** 44x24xh33 Kg.13



**ELECOM24BCLT5DG** 44x14xh33 Kg.12



**ELECOM24BCLT5DGVAL** 58x22xh41 Kg.13



**VALGRU24BCC40DG** 46x33xh18 Kg.8