

Compressore Monocilindrico 12V DC

Interamente in metallo e montato su cuscinetti a sfera, garantisce prestazioni professionali con il minimo ingombro.
motore con protezione termica



One Cylinder Compressor 12V DC

All-metal construction, assembled in ball bearings, ensures professional performances with minimum sizes.
motor thermal protection

CODICE :GRU12CC75AM

DATI TECNICI

Cilindrata 	cmc 75				
Giri/minuto	3157				
	l/min.	cfm		bar	psi
Aria Aspirata/resa	246/221	7.80	a 2	29	
	233/156	5.52	a 6	87	
	236/133	4.71	a 8	116	
Pressione Max 12 bar					
Assorbimento Max	Amp 90				
Potenza media assorbita 6 Bar	Watt 976				
Classe di protezione	IP 20				
Classe di servizio	S1				
Rumorosità	Db 75				
Dimensioni compressore	Cm 32x12xh23				
Peso compressore	Kg.8.2				
Tempo di Carica Serbatoio da 25lt. da 0-a 8 bar :92"					
Raccomandato per uso continuo Max 60 min:					



TECHNICAL DATA

Swept	cmc 75				
Rpm	3157				
	l/min.	cfm		bar	psi
Air intake/Free air delivery	246/221	7.80	a 2	29	
	233/156	5.52	a 6	87	
	236/133	4.71	a 8	116	
Max pressure 12 bar					
Max Amp. absorption	Amp 90				
Average power absorption to 87 psi	Watt 976				
Protection class	IP 20				
Service class	S1				
Noise level	Db 75				
Compressor dimensions	Cm 32x12xh23				
Compressor weight	Kg.8.2				
Charge time of 25 lt tank 0-116 psi:92"					
For Costant working:Max 60 minutes					

I dati sono suscettibili di modifiche senza preavviso - The company reserves the right to change any element without notice.



GRU12CC75AMDIR
Cm32x20xH30