

Compressore Monocilindrico 24V DC

Interamente in metallo e montato su cuscinetti a sfera, garantisce prestazioni professionali con il minimo ingombro.
motore con protezione termica



One Cylinder Compressor 24V DC

All-metal construction, assembled in ball bearings, ensures professional performances with minimum sizes.
motor thermal protection

CODICE :GRU24CC75AM

DATI TECNICI

Cilindrata 	cmc 75				
Giri/minuto	2600				
	l/min.	cfm		bar	psi
Aria Aspirata/resa	197/162	5.73	a	2	29
	193/117	4.13	a	6	87
	197/100	3.53	a	8	116
Pressione Max 12 bar					
Assorbimento Max	Amp 34				
Potenza media assorbita	Watt 636				
Classe di protezione	IP 20				
Classe di servizio	S1				
Rumorosità	Db 70				
Dimensioni compressore	Cm 32x13.5xh23				
Peso compressore	Kg.8.0				
Tempo carica 25lt da 0-8 bar . 120"					
Raccomandato per uso continuo Max 60 min:					



TECHNICAL DATA

Swept	Cmc75				
Rpm	2600				
	l/min.	cfm	a	bar	psi
Air intake/Free air delivery	197/162	5.73	a 2	29	
	193/117	4.13	a 6	87	
	197/100	3.53	a 8	116	
Max pressure 12 bar					
Max Amp. absorption	Amp 34				
Average power absorption	Watt 636				
Protection class	IP 20				
Service class	S1				
Noise level	Db 70				
Compressor dimensions	Cm 32x13.5xh23				
Compressor weight	Kg.8.0				
Charge time of 25 lt tank 0-116 psi:120"					
For Costant working:Max 60 minutes					

I dati sono suscettibili di modifiche senza preavviso - The company reserves the right to change any element without notice.



GRU24CC75AMDIR
Cm 32x20xh30